



OH 40 A



#### Packaging data

Sales unit	1 pcs.
Packaging volume shipping package	23.5 dm <sup>3</sup>
Gross Weight shipping unit	5.45 kg
EAN	4010056731441
Article number	73144
Customs tariff number	85437090

#### Technical data

Frequency range TV	47...862 MHz (output combiner/amplifier)
Frequency range FM	87,5...108 MHz (FM-amplifier)
Input level FM	70...100 dB $\mu$ V
Gain FM	25 dB
Attenuator FM	0...30 dB (1 dB-steps)
Output level	110 dB $\mu$ V
Output attenuator	0...15 dB
Output test jack	-20 dB
Connections	
Module slots	7 pcs. (OH-module)
F-socket	3 pcs. (FM-input, output, output measurement socket)
USB	1 pcs. (Software-Update, Konfiguration)
RJ11	1 pcs. (OH 41)
RJ45	1 pcs. (remote monitoring and programming)
General data	
Operating voltage AC	180...265 V
Power input	<185 W
LNB supply voltage	12.5 V
LNB electrical power supply	1.2 mA
Dimensions (width x height x depth)	276x159x385 mm
Operating temperature range	-20...+50 °C

#### Title

OH 40 A

#### Short description

Compact Headend basic unit, 230 V AC, 19", 3 HE, for 7



modules

Slots for up to 7 modules

Wall mounting

Integrated FM amplifier

Programable with OH 41 hand-set

Update via USB-connection (USB memory stick)

Integrated remote supervision moduel OH 51 A (license optional)